



CAPA102

24VAC-16A16CH

Maxi Cabinet
16A16 Channel CCTV Power Supply



Features

- (16A16) 2 x 8 individually fused outputs (PTC)
- Dual modular redundant design
- Short circuit, high temperature protection
- External LED indicator for each channel, blue for normal operation, red for fault condition
- External power on/off switch for each of the 8 Channels
- Power cable supplied - no hard wiring
- Strong metal cabinet with rear cable access and punch outs for easy installation
- 2 year warranty
- *AS/NZS61588 approval

Specification

Model	24VAC-16A16CH
Number of Channels	2 x 8 Channel
Output Voltage	24VAC + 10%, no load voltage 26+/- 10%
Total Output Current	2 x 8A - 1A per Channel
Total Output Power	2 x 192W
PTC Fuse Rating	2.5A@60V
Protection	
General Protection	Each Output has a PTC fuse with External Bi-Colour LED indicator.
High Temp. Protection	Output shutdown @ 130°C
General Protection	Each Output has a PTC fuse with external bi-colour LED indicator.
Short Circuit Protection	When a short circuit occurs, the Individual PTC Fuse will go open Circuit. Led Indicator will go from blue to red. When the short is removed, the PTC fuse will automatically reset and LED will return to blue.
Operating Temperature	Minus 10 - 40°C maximum
Humidity	20-90% RH
Input Voltage	240VAC @ 50Hz
Thermal Fuse Rating	130°C
Approvals	Ctick, EMC,AS/NZS 61588, 2:6:2009
Dimension (mm)	400H x 400W x 80D