



## 24VAC 16A16CH

1.5 U Rack mount

**16A16 Channel  
CCTV Power Supply**



# Features

- (16A16) 2 x 8 individually fused outputs (PTC)
- Dual modular redundant design
- Short circuit, high temperature protection
- External LED indicator for each channel, **blue** for normal operation, **red** for fault condition
- External power on/off switch for each of the 8 Channels
- Power cable supplied - no hard wiring
- Strong metal cabinet with rear cable access for easy installation
- 2 year warranty
- \*AS/NZS61588 approval

## Specification

Model	24VAC-16A16CH
Number of Channels	2 x 8 Channel
Output Voltage	24VAC + 10%, no load voltage: 26+/- 10%
Total Output Current	2 x 8A - 1A / Channel
Total Output Power	2 x 192W
PTC Fuse Rating	2.5A@60V
<b>Protection</b>	
General Protection	Each Output has a PTC fuse with External Bi-Colour LED indicator.
High Temp. Protection	Output shutdown @ 130°C
Circuit Short Protection	When a short circuit occurs, the Individual PTC Fuse will go open Circuit. Led Indicator will go from <b>blue</b> to <b>red</b> . When the short is removed, the PTC fuse will automatically reset and LED will return to <b>blue</b> .
Compliance	CTICK, AS/NZS 61588