

Part No. PA88-24VAC 12A16



Maxi Cabinet 12A16 Channel CCTV Power Supply Features



- (12A16) 2 x 8 individually fused outputs (PTC)
- Dual modular redundant design
- Short circuit, high temperature protection
- External LED indicator for each channel, blue for normal operation, red for fault condition
- External power on/off switch for each of the 8 Channels
- Power cable supplied - no hard wiring
- Strong metal cabinet with rear cable access and punch outs for easy installation
- 2 year warranty
- *AS/NZS61588 approval



Specification

Model	PA88- 24VAC-12A16	PA88-24VAC-6A8
Number of Channels	2 x 8 Channel	8 Channel
Output Voltage	24VAC + 10%, no load voltage 26+/- 10%	
Total Output Current	2 x 8A - 750mA per Channel	6A - 750mA per Channel
Total Output Power	2 x 144W	144W
PTC Fuse Rating	2.5A@60V	
Protection		
General Protection	Each Output has a PTC fuse with External Bi-Colour LED indicator.	
High Temp. Protection	Output shutdown @ 130°C	
General Protection	Each Output has a PTC fuse with external bi-colour LED indicator.	
Short Circuit Protection	When a short circuit occurs, the Individual PTC Fuse will go open Circuit. Led Indicator will go from blue to red . When the short is removed, the PTC fuse will automatically reset and LED will return to blue .	
Operating Temperature	Minus 10 - 40°C maximum	
Humidity	20-90% RH	
Input Voltage	240VAC @ 50Hz	
Thermal Fuse Rating	135°C	
Approvals	SAA, Ctick, EMC,AS/NZS 61588	
Dimension (mm)	400H x 400W x 80D	