



Part No. PA812-16 PSU

Features

- 100% Full Load Burn in Test
- Protection: Short Circuit and Over Voltage
- Class II Power Supply
- Low Ripple Voltage < 40mV
- Approvals: AS/NZS 60950.1:2003
- 2 Year Warranty

Specifications

Model	PA812-16	
OUTPUT: SMPSU	DC Voltage	11-14V
	Rated Current	8A
	Current Range	0-8A
	Rated Power	96W
	Ripple/Noise	<40mV p-p
OUTPUT: PTC PCB	DC Voltage	12V
	No Of Channels	16 Channel
	Rated Current	1.5A/CHANNEL
	Current Range	0-1.5A/CHANNEL
	Rated Power	96W
INPUT:SMPSU	Voltage Range	200-240VAC
	Frequency	50/60Hz
	Efficiency	95%
	AC Current	3.15A
INPUT:PTC PCB	Voltage Range	11-14V
	Current Range	0-8A
PROTECTION	OVERLOAD	110-150% of rated output power Shut off AC - recycle to restart
ENVIROMENT	WORKING TEMP.	50 degrees
	Humidity	20-90% RH
APPROVALS	SAFETY STANDARD	AS/NZS60950.1:2003
	EMC	Compliance EN55022 ClassB