



Part No. PA817- 4ch PSU

Features

- Dual 7AH Battery Back-Up option.
- 4 Individually Fused Channels
- Short Circuit, Over Load and High Temperature Protection
- Class II Power Supply
- Low Ripple Voltage <40mV
- AC Power Indicator on Front Cover
- Individual LED's for each output
- External Power on /off Switch
- Power Cable Supplied - No hard wiring
- Strong metal cabinet with rear cable access
- and punch outs for easy installation
- 2 Year Warranty

Specifictazion

SPECIFICATION SHEET	MODEL: PA812 SERIES	
Model	PA812-8	
OUTPUT: SMPSU	DC Voltage	11-14V
	Rated Current	8A
	Current Range	0-8A
	Rated Power	96W
	Ripple/Noise	<40mV p-p
OUTPUT: PTC PCB	DC Voltage	12V
	No. of Channels	8 Channel
	Rated Current	1.5A/CHANNEL
	Current Range	0-1.5A/CHANNEL
	Rated Power	96W
INPUT:SMPSU	Voltage Range	200-240VAC
	Frequency	50/60Hz
	Efficiency	95%
	AC Current	3.15A
INPUT:PTC PCB	Voltage Range	11-14V
	Current Range	0-8A
PROTECTION	OVERLOAD	110-150% of rated output power Shut off AC - reccycle to restart
ENVIROMENT	WORKING TEMP.	50 degrees
	Humidity	20-90% RH
APPROVALS	SAFETY STANDARD	AS/NZS60950.1:2003
	EMC	Compliance EN55022 ClassB